


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM3040/WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2552.7 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	3199	3211	3181	3132	3095	3088	3101	3147	0- 10	307.6	307.6	12.1
20	2347	2420	2440	2381	2304	2242	2218	2266	10- 20	790.3	1098	43
30	1072	1093	1101	1081	1054	1029	1018	1042	20- 30	731.4	1829	71.7
40	558.0	586.4	577.6	533.8	492.3	482.7	495.8	528.5	30- 40	510.1	2339	91.6
50	51.42	51.99	51.20	47.10	41.89	39.64	42.02	47.41	40- 50	164.8	2504	98.1
60	22.57	21.96	22.46	22.18	21.51	20.31	20.31	21.51	50- 60	27.76	2532	99.2
70	8.749	8.709	8.994	8.838	8.473	8.002	7.727	8.225	60- 70	14.34	2546	99.7
80	1.285	1.926	2.045	1.749	1.127	1.007	1.029	1.031	70- 80	5.858	2552	100
90	0.1188	0.1126	0.1117	0.1135	0.1702	0.1655	0.1689	0.1654	80- 90	0.5825	2553	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:24 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```