

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5378.2 cd per klm.
(Luminaire orientation as tested.)	-1.0 degrees vertical
	-2.0 degrees horizontal

Beam Spread	At 10% of Imax	63.4V x 63.1H
	At 50% of Imax	33.5V x 33.6H
	At 90% of Imax	13.4V x 13.7H

Beam Flux	Total	2430.7 lumens per klm.
	To 10% of Imax	1919.4 lumens per klm.
	To 50% of Imax	1039.7 lumens per klm.
	To 90% of Imax	216.0 lumens per klm.

Upward LOR	0.0 %
Downward LOR	243.1 %


Luminaire Efficiency(Light Output Ratio)	242.6 %
--	---------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	93M20TL0540/BL	Imax (cd)	806.7
NOMINAL POWER (W)	5	AVAILABILITY (%)	191.5
RATED VOLTAGE (V)	48	Avai. FLUX (lm)	287.3
NOMINAL FLUX (lm)	150	LOR (%)	242.6
LAMPS INSIDE	1	TOTAL FLUX (lm)	363.9
TEST VOLTAGE (V)	48	θ @50% (H,V)	34,34DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.02	0.07	0.12	0.16	0.19	0.22	0.25	0.26	0.27	0.27	0.26	0.25	0.22	0.19	0.16	0.12	0.07	0.02	3.13	0.00
90	0.02	0.07	0.12	0.16	0.19	0.22	0.25	0.26	0.27	0.27	0.26	0.25	0.22	0.19	0.16	0.12	0.07	0.02	3.14	0.00
80	0.02	0.07	0.12	0.16	0.19	0.23	0.25	0.27	0.28	0.28	0.27	0.25	0.23	0.19	0.16	0.12	0.07	0.02	3.17	0.00
70	0.02	0.07	0.12	0.16	0.20	0.23	0.26	0.28	0.30	0.30	0.28	0.26	0.23	0.20	0.16	0.12	0.07	0.02	3.27	0.00
60	0.02	0.07	0.12	0.16	0.20	0.25	0.33	0.43	0.52	0.52	0.44	0.33	0.24	0.20	0.16	0.12	0.07	0.02	4.19	0.00
50	0.02	0.07	0.12	0.16	0.21	0.35	0.66	1.19	1.65	1.60	1.13	0.62	0.33	0.21	0.16	0.12	0.07	0.02	8.70	0.72
40	0.02	0.07	0.12	0.16	0.25	0.60	1.65	3.58	5.36	5.17	3.30	1.48	0.54	0.25	0.16	0.12	0.07	0.02	22.9	17.3
30	0.02	0.07	0.12	0.17	0.31	1.05	3.51	8.40	13.2	12.6	7.49	2.95	0.89	0.30	0.17	0.12	0.07	0.02	51.5	47.4
20	0.02	0.07	0.12	0.17	0.37	1.47	5.29	13.5	21.2	20.3	11.7	4.29	1.18	0.34	0.17	0.12	0.07	0.03	80.4	76.8
10	0.02	0.07	0.12	0.17	0.37	1.48	5.43	13.9	21.7	20.7	11.8	4.33	1.20	0.34	0.18	0.12	0.08	0.03	82.0	78.4
0	0.02	0.07	0.12	0.17	0.32	1.08	3.68	8.77	13.6	12.8	7.48	2.91	0.87	0.30	0.17	0.12	0.08	0.03	52.6	48.5
-10	0.02	0.07	0.12	0.17	0.26	0.59	1.75	3.74	5.38	5.12	3.19	1.40	0.52	0.25	0.17	0.12	0.08	0.03	23.0	17.5
-20	0.02	0.07	0.12	0.17	0.22	0.33	0.62	1.17	1.60	1.53	1.04	0.58	0.33	0.22	0.17	0.12	0.07	0.03	8.41	0.63
-30	0.02	0.07	0.12	0.17	0.21	0.25	0.32	0.42	0.48	0.46	0.39	0.31	0.25	0.21	0.17	0.12	0.07	0.03	4.07	0.00
-40	0.02	0.07	0.12	0.17	0.21	0.24	0.27	0.29	0.30	0.30	0.29	0.27	0.24	0.21	0.17	0.12	0.07	0.03	3.39	0.00
-50	0.02	0.07	0.12	0.17	0.20	0.24	0.26	0.28	0.29	0.29	0.28	0.26	0.24	0.21	0.17	0.12	0.07	0.03	3.34	0.00
-60	0.02	0.07	0.12	0.17	0.20	0.24	0.26	0.28	0.29	0.29	0.28	0.26	0.24	0.20	0.17	0.12	0.07	0.03	3.32	0.00
-70	0.02	0.07	0.12	0.17	0.20	0.24	0.26	0.28	0.29	0.29	0.28	0.26	0.24	0.20	0.17	0.12	0.07	0.03	3.32	0.00
-80	0.02	0.07	0.12	0.17	0.20	0.24	0.26	0.28	0.29	0.29	0.28	0.26	0.24	0.20	0.17	0.12	0.07	0.03	3.32	0.00
-90	0.02	0.07	0.12	0.17	0.20	0.24	0.26	0.28	0.29	0.29	0.28	0.26	0.24	0.20	0.17	0.12	0.07	0.03	3.32	0.00
-90 -80 -70 -60 -50 -40 -30 -20 HORIZONTAL (DEG) 20 30 40 50 60 70 80 90																				
Φ t	0.43	1.30	2.14	2.96	4.31	9.30	25.3	57.3	87.0	83.1	50.2	21.3	8.21	4.22	2.97	2.16	1.32	0.45	364	---
Φ a	0.00	0.00	0.00	0.00	0.00	1.04	18.6	51.3	81.3	77.2	44.0	13.8	0.15	0.00	0.00	0.00	0.00	0.00	---	287

one-half-peak spread: U:17.0,D:16.8 , L:18.0,R:15.9


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	8.93	9.22	9.50	9.51	9.51	9.50	9.48	9.48	9.47	9.48	9.49	9.49	9.49	9.51	9.52	9.52	9.51	9.53	9.54
-85	8.93	9.21	9.50	9.50	9.51	9.49	9.48	9.47	9.47	9.48	9.49	9.49	9.49	9.51	9.53	9.53	9.52	9.53	9.54
-80	8.93	9.21	9.49	9.50	9.51	9.49	9.48	9.48	9.48	9.49	9.51	9.50	9.50	9.52	9.55	9.54	9.53	9.54	9.55
-75	8.93	9.20	9.48	9.50	9.51	9.50	9.50	9.49	9.49	9.50	9.52	9.52	9.51	9.53	9.55	9.55	9.54	9.55	9.57
-70	8.93	9.19	9.46	9.51	9.51	9.51	9.50	9.50	9.49	9.50	9.53	9.54	9.53	9.55	9.57	9.57	9.56	9.57	9.59
-65	8.93	9.18	9.45	9.51	9.51	9.50	9.50	9.50	9.49	9.51	9.54	9.55	9.55	9.57	9.60	9.60	9.60	9.61	9.63
-60	8.93	9.17	9.43	9.51	9.50	9.49	9.51	9.51	9.51	9.52	9.55	9.58	9.59	9.61	9.64	9.65	9.64	9.66	9.68
-55	8.93	9.16	9.40	9.51	9.50	9.50	9.52	9.52	9.53	9.54	9.58	9.61	9.63	9.68	9.76	9.80	9.81	9.83	9.84
-50	8.93	9.14	9.37	9.51	9.51	9.52	9.53	9.54	9.56	9.58	9.61	9.69	9.75	9.86	10.1	10.6	10.8	11.0	11.0
-45	8.93	9.13	9.34	9.52	9.52	9.54	9.54	9.56	9.59	9.61	9.72	9.83	10.2	11.1	12.4	13.8	14.6	15.0	15.0
-40	8.93	9.11	9.30	9.51	9.53	9.54	9.55	9.58	9.61	9.72	9.90	10.7	12.2	14.4	17.1	20.0	23.2	24.7	24.6
-35	8.93	9.09	9.26	9.45	9.54	9.55	9.57	9.60	9.70	9.85	10.7	12.5	15.7	20.5	27.8	36.9	45.4	49.9	51.2
-30	8.93	9.07	9.22	9.39	9.54	9.57	9.59	9.63	9.77	10.3	12.5	16.0	22.5	35.3	52.6	72.2	86.4	95.2	98.4
-25	8.93	9.05	9.18	9.33	9.48	9.58	9.61	9.70	9.92	11.4	15.0	21.4	36.1	60.5	91.6	123	153	172	177
-20	8.93	9.02	9.13	9.26	9.39	9.54	9.63	9.77	10.2	12.9	18.1	29.8	55.1	94.2	142	199	255	294	301
-15	8.93	9.00	9.08	9.19	9.30	9.43	9.57	9.80	10.8	14.3	21.4	39.9	76.5	130	203	297	389	456	468
-10	8.93	8.98	9.03	9.11	9.21	9.32	9.45	9.70	11.2	15.5	25.4	49.8	94.6	164	269	400	531	623	645
-5	8.93	8.95	8.98	9.04	9.11	9.20	9.34	9.59	11.3	16.1	27.4	55.7	107	192	321	481	639	745	772
0	8.93	8.93	8.93	8.96	9.01	9.08	9.21	9.48	11.2	16.2	27.7	56.9	110	197	332	503	671	781	807
5	8.93	8.93	8.93	8.96	9.01	9.09	9.22	9.48	11.1	15.8	26.9	54.7	105	186	309	466	621	724	753
10	8.93	8.93	8.93	8.97	9.01	9.09	9.21	9.46	10.8	15.0	24.7	48.6	92.4	160	257	383	512	601	626
15	8.93	8.93	8.94	8.97	9.01	9.08	9.21	9.44	10.3	13.9	21.1	39.3	73.3	122	194	284	375	441	459
20	8.93	8.93	8.94	8.97	9.01	9.08	9.19	9.40	9.89	12.5	18.1	29.5	52.2	87.4	133	189	247	290	300
25	8.93	8.93	8.94	8.97	9.01	9.07	9.16	9.32	9.62	11.1	15.2	22.1	35.9	56.6	84.3	118	150	174	178
30	8.93	8.93	8.94	8.97	9.01	9.06	9.13	9.23	9.46	10.2	12.8	17.1	24.3	35.7	51.0	69.1	85.9	97.9	98.7
35	8.93	8.93	8.94	8.97	9.00	9.04	9.10	9.19	9.36	9.62	10.9	13.5	17.2	22.3	29.5	37.9	46.5	52.0	52.5
40	8.93	8.93	8.94	8.97	8.99	9.02	9.08	9.14	9.24	9.43	9.76	11.0	13.0	15.5	18.5	21.2	24.6	26.7	27.3
45	8.93	8.93	8.95	8.96	8.98	9.00	9.05	9.10	9.17	9.25	9.43	9.63	10.3	11.5	12.9	14.0	15.3	16.2	16.5
50	8.93	8.93	8.95	8.96	8.97	8.99	9.03	9.07	9.12	9.17	9.24	9.37	9.47	9.68	10.0	10.5	11.0	11.4	11.5
55	8.93	8.93	8.95	8.96	8.97	8.98	9.01	9.04	9.07	9.11	9.15	9.19	9.25	9.34	9.41	9.46	9.52	9.56	9.58
60	8.93	8.93	8.95	8.95	8.96	8.98	8.99	9.02	9.04	9.07	9.09	9.11	9.14	9.17	9.18	9.21	9.26	9.29	9.29
65	8.93	8.94	8.95	8.95	8.96	8.97	8.98	8.99	9.01	9.02	9.04	9.05	9.07	9.08	9.10	9.11	9.13	9.15	9.15
70	8.93	8.94	8.95	8.96	8.96	8.97	8.98	8.98	8.99	9.00	9.00	9.01	9.02	9.03	9.04	9.05	9.06	9.07	9.08
75	8.93	8.94	8.95	8.95	8.96	8.97	8.98	8.98	8.98	8.98	8.98	8.98	8.99	8.99	9.00	9.01	9.01	9.02	9.03
80	8.93	8.94	8.95	8.95	8.95	8.96	8.98	8.97	8.97	8.97	8.97	8.97	8.97	8.97	8.98	8.98	8.98	8.99	9.00
85	8.93	8.94	8.95	8.95	8.95	8.96	8.98	8.97	8.96	8.96	8.96	8.96	8.96	8.96	8.96	8.97	8.97	8.98	8.99
90	8.93	8.94	8.96	8.95	8.95	8.96	8.97	8.96	8.96	8.96	8.96	8.96	8.96	8.96	8.96	8.97	8.97	8.98	8.99

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	9.53	9.52	9.50	9.48	9.49	9.49	9.51	9.52	9.51	9.50	9.49	9.49	9.49	9.49	9.49	9.49	9.49	9.49	
-85	9.53	9.53	9.50	9.48	9.50	9.51	9.51	9.51	9.50	9.49	9.49	9.48	9.49	9.49	9.49	9.49	9.49	9.49	
-80	9.54	9.52	9.52	9.51	9.51	9.52	9.51	9.51	9.51	9.50	9.50	9.49	9.49	9.49	9.49	9.49	9.49	9.49	
-75	9.55	9.54	9.53	9.52	9.52	9.52	9.52	9.52	9.51	9.50	9.50	9.50	9.50	9.50	9.50	9.49	9.49	9.49	
-70	9.58	9.56	9.55	9.54	9.54	9.55	9.55	9.54	9.53	9.51	9.51	9.50	9.50	9.50	9.50	9.49	9.50	9.49	
-65	9.61	9.59	9.57	9.56	9.57	9.57	9.57	9.56	9.54	9.53	9.52	9.51	9.51	9.51	9.50	9.50	9.50	9.49	
-60	9.66	9.64	9.61	9.60	9.60	9.60	9.59	9.58	9.56	9.54	9.53	9.53	9.52	9.51	9.51	9.50	9.50	9.49	
-55	9.81	9.78	9.74	9.72	9.69	9.64	9.63	9.60	9.58	9.56	9.54	9.54	9.53	9.52	9.51	9.50	9.50	9.49	
-50	10.8	10.6	10.3	10.0	9.88	9.78	9.73	9.63	9.61	9.58	9.56	9.55	9.54	9.52	9.51	9.50	9.50	9.49	
-45	14.4	13.6	12.8	12.0	11.0	10.3	9.87	9.75	9.63	9.61	9.58	9.57	9.55	9.53	9.51	9.51	9.50	9.49	
-40	23.2	21.1	18.3	16.2	14.1	12.3	10.8	9.95	9.73	9.63	9.60	9.58	9.56	9.54	9.51	9.51	9.50	9.49	
-35	47.9	41.5	32.6	25.1	19.6	15.5	12.7	10.8	9.84	9.70	9.63	9.59	9.57	9.54	9.52	9.51	9.50	9.49	
-30	91.4	79.2	60.8	44.1	30.8	21.2	15.6	12.4	10.3	9.76	9.64	9.61	9.58	9.55	9.52	9.50	9.50	9.49	
-25	164	139	104	73.5	47.9	30.5	19.7	14.3	11.2	9.89	9.69	9.62	9.58	9.55	9.52	9.50	9.51	9.49	
-20	276	227	172	113	72.2	43.5	25.3	16.6	12.3	10.1	9.75	9.63	9.59	9.56	9.53	9.50	9.51	9.49	
-15	428	346	252	166	102	59.0	32.2	19.0	13.4	10.5	9.79	9.64	9.59	9.56	9.53	9.50	9.51	9.49	
-10	588	473	338	217	129	73.9	39.9	21.9	14.4	10.9	9.82	9.65	9.59	9.56	9.53	9.50	9.51	9.49	
-5	708	571	403	257	156	84.7	44.7	23.7	15.1	11.2	9.83	9.65	9.59	9.56	9.53	9.51	9.51	9.49	
0	747	605	429	272	158	87.1	46.1	24.3	15.4	11.3	9.84	9.64	9.59	9.56	9.52	9.51	9.51	9.49	
5	692	560	401	256	148	81.9	44.0	23.7	15.1	11.1	9.73	9.53	9.48	9.47	9.46	9.46	9.48	9.49	
10	574	466	335	217	131	73.0	39.8	22.1	14.5	10.8	9.61	9.41	9.37	9.37	9.39	9.41	9.46	9.49	
15	422	345	252	170	102	59.5	33.3	19.5	13.5	10.4	9.48	9.29	9.26	9.28	9.32	9.37	9.44	9.49	
20	279	230	172	118	75.6	44.9	26.2	17.0	12.4	9.95	9.42	9.20	9.15	9.19	9.25	9.32	9.42	9.49	
25	166	140	109	77.3	51.2	32.1	20.2	14.5	11.2	9.66	9.33	9.17	9.09	9.10	9.19	9.28	9.39	9.49	
30	93.2	80.0	64.4	47.3	32.7	22.2	15.9	12.4	10.1	9.48	9.23	9.13	9.07	9.02	9.12	9.24	9.37	9.49	
35	50.1	44.3	36.2	28.0	20.9	16.1	12.9	10.7	9.61	9.36	9.19	9.10	9.05	9.02	9.06	9.20	9.35	9.49	
40	26.6	24.5	21.1	18.0	15.0	12.5	10.7	9.71	9.42	9.24	9.14	9.07	9.04	9.01	9.00	9.16	9.33	9.49	
45	16.4	15.7	14.4	13.0	11.4	10.2	9.60	9.42	9.25	9.17	9.10	9.05	9.02	9.00	8.99	9.12	9.32	9.49	
50	11.6	11.3	10.7	10.1	9.73	9.48	9.36	9.24	9.17	9.11	9.07	9.03	9.00	8.99	8.98	9.09	9.30	9.49	
55	9.59	9.57	9.53	9.48	9.38	9.26	9.20	9.15	9.11	9.07	9.04	9.01	8.99	8.99	8.98	9.07	9.29	9.49	
60	9.29	9.28	9.25	9.23	9.20	9.16	9.11	9.08	9.06	9.04	9.02	9.00	8.98	8.98	8.97	9.04	9.27	9.49	
65	9.15	9.15	9.13	9.11	9.10	9.09	9.06	9.04	9.02	9.01	9.00	8.99	8.98	8.98	8.97	9.02	9.26	9.49	
70	9.08	9.07	9.07	9.06	9.05	9.04	9.02	9.00	8.99	8.99	8.98	8.97	8.97	8.97	8.97	9.00	9.25	9.49	
75	9.03	9.02	9.02	9.02	9.01	9.01	8.98	8.97	8.98	8.97	8.97	8.96	8.97	8.97	8.97	8.99	9.24	9.49	
80	9.00	9.00	9.00	9.00	8.99	8.99	8.98	8.97	8.97	8.97	8.96	8.96	8.97	8.97	8.97	8.97	9.23	9.49	
85	8.99	9.00	8.99	8.98	8.98	8.98	8.97	8.95	8.96	8.96	8.96	8.96	8.96	8.97	8.96	8.97	9.23	9.49	
90	8.98	8.98	8.98	8.97	8.98	8.98	8.96	8.94	8.95	8.97	8.96	8.96	8.96	8.96	8.96	8.96	9.22	9.49	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: