


LAMP PHOTOMETRIC REPORT

MODEL: 95Livia90/GR		
POWER: 6W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 427.95 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	374.3	380.7	383.1	379.3	371.7	362.6	364.0	368.7	0- 10	37.86	37.86	8.85
20	274.2	284.4	282.4	275.7	266.3	261.0	264.0	270.2	10- 20	90.24	128.1	29.9
30	180.1	187.2	185.1	180.7	173.0	172.1	178.0	179.1	20- 30	102.5	230.6	53.9
40	110.2	112.5	112.4	112.5	106.6	103.9	109.2	110.0	30- 40	88.84	319.5	74.7
50	62.82	61.96	62.40	65.21	60.82	57.06	60.46	62.54	40- 50	64.64	384.1	89.8
60	31.11	30.24	30.90	33.42	31.06	27.87	28.78	30.57	50- 60	40.18	424.3	99.1
70	0	0	0	0	0	0	0	0	60- 70	3.665	428.0	100
80	0	0	0	0	0	0	0	0	70- 80	0	428.0	100
90	0	0	0	0	0	0	0	0	80- 90	0	428.0	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 December 2022

γ Range: 0 - 60DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```